



RINGO STAR SLIM
SUSPENDED



DE LED-Pendelleuchte. Direkt-indirektstrahlend. Opal diffusor aus satiniertem Acrylglas. Leuchtenkorpus aus Aluminiumprofil wahlweise weiß, silber, graphit, schwarz, titan oder kupferfarben lackiert. Konverter in Deckenbaldachin integriert, wahlweise einfach schaltbar oder stufenlos dimmbar (1-10V, DALI, Touch-Dim, Casambi). Standard-Farbtemperatur 2200K, 2700K, 3000K, 3500K, 4000K oder 6500K. Binning initial ≤ MacAdam 3. Farbwiedergabe Ra>80, alternativ Ra>90. Seilpendel-Set stufenlos höhenverstellbar.


EN Suspended LED Light. Direct-indirect or direct only light distribution. Opal diffuser made of satin acrylic glass for general lighting. Luminaire body made of aluminum profile optionally available in white, silver, graphite, black, titanium or copper colours. Converter integrated in ceiling rose, optional switched or dimmed (1-10V, DALI, Touch-Dim, Casambi). Standard colour temperature 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI> 80, alternative CRI> 90. For installation with cord suspension.

FR Luminaire en suspension LED. Éclairage DIRECT-INDIRECT. Diffuseur opale en verre acrylique satiné. Corps du luminaire en profilé aluminium disponible en blanc, argent, graphite, noir, titane ou cuivre laqué. Convertisseur intégré dans la patère, allumage simple ou gradable au choix(1-10V, DALI, Touch-Dim, Casambi). Températures de couleur standard 2200K, 2700K, 3000K, 3500K, 4000K ou 6500K. Binning ≤ MacAdam 3. Rendu des couleurs IRC> 80, IRC> 90 sur demande. Kit de filins-suspensions réglables en hauteur.




PRODUCT-CODE:		R	P	6	O	S	D	-	8	3	0	M	-	D	1	5	0	0	-	U
PRODUCT FAMILY	R: Ringo Star																			
TYPE	P6: Direct-Indirect, G6: Direct-Only																			
OPTICAL SYSTEM	O: Opal																			
SURFACE FINISH	W: Snow White, V: Ivory White, S: Radiant Silver, U: Urban Graphite, B: Jet Black, T: Satin Titanium, K: Satin Copper																			
CONTROL GEAR	E: On/Off, L: DALI, D: 1-10V, H: Touch-Dim, C: Casambi																			
COLOUR REND.	8: CRI>80, 9: CRI>90																			
COLOUR TEMP.	22: 2200K, 27: 2700K, 30: 3000K, 35: 3500K, 40: 4000K, 65: 6500K																			
POWER	M: Medium Power, H: High Power																			
SIZE	Luminaire Diameter in mm: D1000, D1500, D2000																			
SUSPENSION	U: Central Cord Suspension, K: Parallel Cord Suspension																			

OPAL DIFFUSER / DIRECT



D mm	Lumen/Watt Medium Power
1000	4860lm/48W
1500	7450lm/72W
2000	10042lm/96W

OPAL DIFFUSER / DIRECT-INDIRECT



D mm	Lumen/Watt Medium Power
1000	8275lm/76W
1500	12575lm/112W
2000	16875lm/149W

Lumen Values: Luminaire luminous flux at 4000K/CRI>80. Other configurations on request.

